

(19)



LE GOUVERNEMENT  
DU GRAND-DUCHÉ DE LUXEMBOURG  
Ministère de l'Économie

(11)

N° de publication :

**93102**

(12)

**BREVET D'INVENTION****B1**

(21)

N° de dépôt: 93102

(51)

Int. Cl.:  
A61N 5/10

(22)

Date de dépôt: 10/06/2016

(30)

Priorité:

(43)

Date de mise à disposition du public: 22/01/2018

(47)

Date de délivrance: 22/01/2018

(73)

Titulaire(s):  
FYZIKALNI USTAV AV CR, V.V.I. – 18221 PRAHA  
8 (République tchèque)

(72)

Inventeur(s):

GRITTANI GABRIELE MARIA – 25241 DOLNI  
BREZANI (République tchèque), KORN GEORG –  
25241 DOLNI BREZANI (République tchèque),  
LAZZARINI CARLO MARIA – 25241 DOLNI  
BREZANI (République tchèque), LEVATO TADZIO –  
25241 DOLNI BREZANI (République tchèque)

(74)

Mandataire(s):


DENNEMEYER & ASSOCIATES S.A. PATENT  
DEPARTMENT – 1015 LUXEMBOURG (Luxembourg)

(54)

**Dispositif et procédé pour une radiothérapie par impulsion à dose élevée avec une imagerie à temps réel.**

(57)

ABSTRACT: A radiotherapy system comprising at least one pulsed radiation source, at least one imaging system, a control system, and a synchronization system is disclosed. The pulsed radiation source deposits high dose radiation pulses to a target region inside the patient; simultaneously the imaging system is used to monitor the target region, synchronized by the synchronization system. The dose per radiation pulse is high enough to deposit, within few pulses, 1 Gy at a depth of at least 1 cm in water. At each irradiation time step, the pulsed radiation source delivers short pulses of radiation ( $< 1$  ms) and the imaging system performs a snapshot of the position, and eventually the shape, of the target region during the irradiation time, with a time resolution better than 200 ms. Being both the pulsed radiation source and imaging system synchronized by the synchronization system with less than 200 ms jitter, this system allows for very precise reconstruction of the map of the dose deposited into the target region. 93102



# DEVICE AND METHOD FOR HIGH DOSE PER PULSE RADIOTHERAPY WITH REAL TIME IMAGING

## FIELD OF THE INVENTION

The invention relates to a radiotherapy system which allows the monitoring of the position of the target region during the treatment and thus allowing effective radiotherapeutic treatment.

## BACKGROUND OF THE INVENTION

Radiotherapy is an important treatment for many types of cancer. This technique relies on the use of radiation sources to deliver dose to a target region within the patient's body. Furthermore, radiotherapy is not restricted only to cancer treatment, but can be applied in general to deliver dose to a target region within the patient's body as in the case, for example, of radiosurgery.

In the state of the art, radiotherapy is, in most of the cases, performed using radio frequency accelerators, which are devices capable of delivering electron or gamma beams with energy typically in the range 6-30 MeV. Due to their technology, these devices usually deliver very wide beams on the order of  $10 \times 10 \text{ cm}^2$  and a dose rate of few Gy/min. Typically, such devices deliver to the target region 0.1-1 mGy per pulse, at a frequency of few hundreds Hz. Treatments with these devices usually last at least few minutes. During this time the target region within the patient's body can move, due, for example, to patient's breathing. For this reason huge effort is put in imaging the target region during the treatment.

Patent US 9,044,604 discloses a radiotherapy system including a radiotherapy module and at least one X-ray imaging module. Using radio frequency accelerators, due to the low dose per pulse and to the high number of pulses needed, it is not feasible to perform radiography at each irradiation step. One of the reasons is that each radiography delivers additional dose to the patient.

Patent US 8,039,819 discloses a device for creating a spatial dose distribution in a medium volume, the device comprising a laser system and at least one electron source for releasing a plurality of high-energy quasi-monoenergetic electron pulses upon irradiation with said laser pulses. The disclosed device produces ultra-short radiation pulses ( $< 1 \text{ ms}$ ) with very high energy ( $> 50 \text{ MeV}$ ), but it is lacking a synchronized imaging system and a feedback control that exploits the treatment effectiveness due to the shortness of the radiation pulses.

## DISCLOSURE OF THE INVENTION

The present invention provides a system for radiotherapy which comprises at least one pulsed radiation source for delivering radiation pulses shorter than 1 ms, at least one imaging system, at least one control system for determining the deposited dose, and at least one synchronization system for

synchronizing said pulsed radiation source and said imaging system within a time jitter shorter than 200 ms, wherein said pulsed radiation source is capable of delivering a dose of at least 50 mGy at a depth of at least 1 cm in water within a single pulse, wherein said imaging system has the time resolution better than 200 ms, and wherein said control system is connected to the pulsed radiation source and to the imaging system.

The system of the present invention, by enabling depositing in a target region of a very high dose per pulse, by imaging the target region during each irradiation time step, and by retrieving the dose deposited map after each irradiation time step, allows to achieve a very effective treatment because it allows to determine the dose deposited in the individual parts of the treated region of the body, and the position of the target region after each irradiation time step is monitored, hence allowing adapting and improving the treatment plan after any irradiation time step, whenever necessary. By delivering higher dose per pulse, it is possible to perform a patient treatment session with just few radiation pulses. Using a synchronized imaging system, it is possible to gain information about the position, and eventually the shape, of the target region during each irradiation time step. This synchronized imaging helps to understand how precisely the target region has been irradiated, and this information can be used for improving the dose delivery in the subsequent pulses. Furthermore, this imaging may be used to foresee the target region position, and eventually shape, for the following radiation pulses.

With a radiation pulse shorter than 1 ms, with the time resolution of the imaging system shorter than 200 ms, and with the time jitter between them shorter than 200 ms, the target region irradiation and imaging happens in a time window smaller than 400 ms. Said time resolution is short enough that most of the patient's body internal structure can be considered still.

In this way it is possible to image the position, and optionally the shape, of the target region, with respect, for example, to markers and/or internal organs or bones of the patient's body, within an overall time window of less than 400 ms. After processing the data from the imaging system and the pulsed radiation source, it is possible to retrieve the dose deposited distribution in the target region and, eventually, in the patient's body. This information can be used to modify, according to patient specific needs, the patient's treatment plan. For this reason the invention disclosed herein brings advantages in the direction of Personalized Medicine.

By combining the imaging data with the radiation pulse data, a map of the dose deposited into the patient's body can be reconstructed with a very high accuracy due to the fact that the patient is still during the whole irradiation and imaging process. The reconstruction of the deposited dose map can be done either after each radiation pulse, after few of them or after the whole treatment session. The advantage is that this provides a better understanding of where the dose has been really deposited into the patient's body. In particular, performing a reconstruction of the dose deposited after one or more radiation pulses, and adjusting the treatment plan according to this information after one or more

pulses, can lead to an higher dose deposited into the target region and to a lower dose deposited in the surroundings of the target region, inside the patient's body. This method can be more effective than conventional methods in performing a more personalized treatment.

5 In a preferred embodiment, the synchronization system is an electrical device capable of sending electrical pulses synchronized with a tunable delay within a time resolution better than 200 ms.

The pulsed radiation source creates and delivers radiation beams to the patient. Each pulse of radiation is shorter than 1 ms and delivers a dose of at least 50 mGy at a depth of at least 1 cm in water.

10 The pulsed radiation source can preferably be selected from the group comprising sources of electron beams, sources of high energy photon beams, sources of positron beams, sources of neutron beams, sources of pi meson beams, sources of beams comprising combinations of these particles.

The pulsed radiation source can in one embodiment comprise a laser plasma electron accelerator. The electron beam emitted from the accelerator can be used as the radiation beam, or may be converted in the pulsed radiation source into a beam of high energy photons, positrons, neutrons or pi mesons, or of a mixture of these particles.

15 The pulsed radiation source may comprise a laser emission system, a laser transport, a laser focusing system, a plasma electron accelerator, a radiation beam delivery system. In one embodiment, the radiation beam delivery system is adapted for checking the electron beam quality and/or stopping or modifying the beam in order to achieve pre-determined criteria (e.g., determined by the treatment plan). In one embodiment, the radiation beam delivery system may use the kinetic energy of the  
20 electron beam to create a different particle beam, for example a beam of high energy photons, positrons, neutrons or pi mesons.

In a preferred embodiment, the laser emission system is a Ti:Sa laser, for delivering laser pulses with energy of at least 100 mJ and pulse duration shorter than 1  $\mu$ s; more particularly a Ti:Sa laser, pumped by diode pumped solid state lasers with frequency conversion, for delivering laser pulses with  
25 energy of at least 100 mJ and pulse duration shorter than 1  $\mu$ s.

In a preferred embodiment, the laser transport comprises at least one system selected from: a compressor for compressing the laser pulse in time to less than 100 fs, and an optical transport line for sending the laser pulse to the laser focusing system; a compressor, an optical transport line and a phased optical fiber array for transporting an uncompressed laser pulse with time duration of at least  
30 10 ps to the compressor, whereas the compressor is capable of compressing the laser pulse in time to less than 100 fs and then sending the laser pulse to the optical transport line for sending the laser pulse to the laser focusing system.

In a preferred embodiment, the laser focusing system may be an optical system for focusing the laser pulses into the plasma electron accelerator, comprising at least one positioning mirror and at least one off-axis parabola capable of focusing the laser pulses to intensity higher than  $10^{12}$  W/cm<sup>2</sup>.

5 In another preferred embodiment, the laser focusing system is an optical system for focusing the laser pulses into the plasma electron accelerator, comprising at least one positioning mirror and at least one spherical mirror capable of focusing the laser pulses to intensity higher than  $10^{12}$  W/cm<sup>2</sup>.

In a preferred embodiment, the plasma electron accelerator is a device comprising at least one gas target mounted on a remotely controlled motorized stage with at least one degree of freedom to align the gas target according to the laser focus.

10 In a preferred embodiment, the radiation beam delivery system comprises at least one of the following components: a magnetic field for selecting the energy of the beam and for optionally shaping the beam, a beam charge diagnostic, a magnetic system for changing the size of the beam, and optionally for focusing or defocusing it, and a solid target converter for generating other particle beams.

The pulsed radiation source may preferably comprise at least one laser beam diagnostic, selected from:  
15 a spectral shape diagnostic for measuring the spectral shape of the laser pulse; an energy diagnostic for measuring the energy of the laser pulse; a beam shape diagnostic for measuring the energy distribution of the laser pulse along its transverse section; a spectral phase diagnostic for measuring the spectral phase of the laser pulse; a temporal profile diagnostic for measuring the temporal profile of the laser pulse; a laser focal spot diagnostic for measuring the spatial distribution of the laser pulse in its focus;  
20 and a wavefront diagnostic for measuring the phase front of the laser pulse.

In a preferred embodiment, the spectral shape diagnostic can be an optical and/or infrared light spectrometer.

Preferably, the energy diagnostic comprises a calorimeter; and/or at least one optical diode.

25 In a preferred embodiment, the beam shape diagnostics comprises a set of mask filters; and/or a camera and imaging optics.

In a preferred embodiment, the spectral phase diagnostic comprises at least one of the following devices: SPIDER, FROG, D-SCAN and GRENOUILLE.

In a preferred embodiment, the temporal profile diagnostic comprises at least one of the following devices: SPIDER, FROG, D-SCAN and GRENOUILLE.

30 In a preferred embodiment, the electron beam shape diagnostic comprises a fluorescent screen coupled with a CCD.

In a preferred embodiment of the device, the electron beam charge diagnostic comprises at least one Integrating Current Transformer and/or at least one fluorescent screen coupled with a CCD.

In a preferred embodiment, the electron beam spectral shape diagnostic comprises a magnetic dipole and a fluorescent screen coupled with a CCD.

- 5 In a preferred embodiment, the laser focal spot diagnostic comprises a CCD and a reflective object.

In a preferred embodiment, the wavefront diagnostic comprises a wavefront sensor.

- 10 The pulsed radiation source may further comprise a gas target for emitting the electron pulses, which can optionally be monitored by one or more diagnostics selected from a plasma diagnostic for measuring the plasma density inside the target; a laser plasma coupling diagnostic for measuring the coupling in the laser plasma interaction; and a laser propagation diagnostic for measuring the laser propagation after the plasma.

- 15 The electron pulses accelerated by the plasma electron accelerator can preferably be monitored by one or more diagnostics selected from an electron beam shape diagnostic for measuring the transverse shape of the electron pulse; a beam charge diagnostic for measuring the charge of the electron pulse; an electron beam spectral shape diagnostic for measuring the spectral shape of the electron pulse; a beam divergence diagnostic for measuring the divergence of the electron pulse; and a beam temporal profile diagnostic for measuring the temporal profile of the electron pulse.

In a preferred embodiment, the plasma diagnostic comprises at least one CCD with imaging optics looking at the gas target.

- 20 In a preferred embodiment, the laser propagation diagnostic comprises a CCD looking at the laser exiting the target.

In a preferred embodiment, the laser plasma coupling diagnostic comprises a CCD with imaging optics looking at the light emitted by the target.

- 25 In a preferred embodiment, the beam divergence diagnostic comprises a fluorescent screen coupled with a CCD.

In a preferred embodiment, the beam temporal profile diagnostic comprises a streak camera with a resolution better than 10 ps.

In another embodiment, the beam temporal profile diagnostic comprises an infrared spectrometer and a solid target.

The pulsed radiation source may further comprise a control system for the electron beam optimization for collecting the data from all diagnostics, analyzing said data and optionally saving the results. If the electron beam does not satisfy the parameters required for the treatment, the control system for the electron beam optimization modifies the position or state of the pulsed radiation source components until the electron beam reaches the parameters desired.

The pulsed radiation source may preferably comprise at least one of the following components: a spectral shaping device for modifying the spectral shape of the laser pulses; an energy attenuator for changing the energy of the laser pulses; a spectral phase shaper for modifying the spectral phase of the laser pulses; compressor gratings motors for changing the temporal profile of the laser pulses; positioning motors for modifying the path of the laser pulses in the laser focusing system; focusing optics motors for modifying the position and the shape of the laser focal spot; a gas density shaper for modifying the density profile of the gas target; gas target motors for changing the position of the gas target within the plasma electron accelerator; adaptive optics for modifying the wavefront of the laser pulse and so also the shape of the focal spot; a radiation spectrum fine shaper for modifying the spectrum of the radiation pulse; a radiation pulse particle number controller for adjusting the number of particles in the radiation pulse; a radiation pulse spatial distribution shaper for modifying the spatial distribution of the radiation pulse; a radiation pulse divergence controller for adjusting the divergence of the radiation pulse; and a radiation pulse temporal profile controller for adjusting the temporal profile of the radiation pulse. The control system for the electron beam optimization is adapted to operate on at least one of these pulsed radiation source components and/or it is connected to at least one of these pulsed radiation source components.

In a preferred embodiment, the spectral shaping device is a mazzler.

Preferably, the spectral shaping device comprises at least one colored optical filter; and/or at least one prism and at least one neutral optical filter.

In a preferred embodiment, the energy attenuator comprises at least one half-lambda plate and at least one polarizer.

In a preferred embodiment, the spectral phase shaper is a dazzler.

In a preferred embodiment, the adaptive optics comprises a deformable mirror.

In a preferred embodiment, the compressor gratings motors are at least one linear stage mounted below one of the gratings to change the optical path of the different wavelengths.

In a preferred embodiment, the positioning motors are at least one actuator mounted on at least one mirror mount capable of moving with at least one degree of freedom the at least one positioning mirror.

In a preferred embodiment, the focusing optics motors comprise at most five rotation stages and at most seven linear stages mounted below the focusing optics, capable of moving the focusing optics with at least one degree of freedom.

5 In a preferred embodiment, the gas density shaper is a device capable of changing the spatial density of the gas target, comprising at least one of the following components: a gas pressure regulator, a gas mixture regulator, and at least one wire and/or at least one sharp edge, remotely controlled and eventually automatic, that modifies the trajectory of the supersonic gas jet, thus changing the plasma density profile.

10 In a preferred embodiment, the gas target motors are a set of at least one linear stage capable of moving the gas target with at least one degree of freedom.

In a preferred embodiment, the radiation spectrum fine shaper comprises at least one magnetic field and at least one slit.

In a preferred embodiment, the radiation pulse particle number controller comprises at least one magnetic field and at least one slit.

15 In another embodiment, the radiation pulse particle number controller comprises at least one solid target and at least one slit.

In a preferred embodiment, the radiation pulse spatial distribution shaper comprises at least one solid target.

20 In a preferred embodiment, the radiation pulse divergence controller comprises at least one magnetic field and at least one slit.

In another embodiment, the radiation pulse divergence controller comprises at least one solid target and at least one slit.

In a preferred embodiment, radiation pulse temporal profile controller comprises at least one magnetic field.

25 In a preferred embodiment, radiation pulse temporal profile controller comprises at least one solid target.

In a preferred embodiment, the device is controlled by a wireless device, for example a tablet or a laptop.



The pulsed radiation source may, for example, comprise a laser master oscillator, a booster, a stretcher, a first amplifier, a laser pulse delivery system, a final amplifier, a laser transport, a laser focusing system, a plasma electron accelerator, a radiation beam delivery system.

5 The pulsed radiation source may comprise one radiation arm or a plurality of radiation pulse arms, such as two, three, four, five, or more radiation pulse arms. Each of the radiation pulse arms may for example comprise a final amplifier, a laser transport, a laser focusing system, a plasma electron accelerator, a radiation beam delivery system.

In a preferred embodiment, the laser master oscillator is a Ti:Sa oscillator.

10 In a preferred embodiment, the booster comprises a laser pulse amplifier, for example a regenerative amplifier or a multi-pass amplifier.

In a preferred embodiment of the device, the stretcher is an optical device comprising at least one pair of diffractive gratings.

15 In a preferred embodiment, the first amplifier and/or the final amplifier comprises a Ti:Sa crystal pumped by a diode pumped solid state laser with frequency conversion and/or a Ti:Sa crystal pumped by a flash lamp pumped solid state laser with frequency conversion.

In a preferred embodiment of the device, the laser pulse delivery system is an optical system composed by a set of fast flip mirrors. In another embodiment of the device, the laser pulse delivery system is a fast rotating mirror. In another embodiment of the device, the laser pulse delivery system comprises at least one galvo mirror.

20 The imaging system is synchronized with the pulsed radiation source by means of the synchronization system within a time jitter shorter than 200 ms. The imaging system can be based on various imaging technologies known to the person skilled in the art. By way of example, x-ray imaging technology, magnetic resonance imaging (MRI) technology, ballistic and snake photon technology, fluorescent markers, or Cerenkov radiation detection can be used, or a combination of any two or more of these  
25 methods.

In one embodiment, real time magnetic resonance systems capable of imaging may be used to monitor the target region with a time resolution better than 200 ms. The MRI is synchronized to the radiation pulse by the synchronization system with a time jitter lower than 200 ms.

30 In another embodiment, x-ray imaging system is used, wherein a synchronized x-ray source is adapted to emit x-ray for imaging in a time shorter than 200 ms. Thus, x-ray images are acquired with a time resolution better than 200 ms. The x-ray imaging system is synchronized to the radiation pulse by the synchronization system with a time jitter lower than 200 ms.

During the x-ray imaging, the additional dose deposited into the patient's body due to the imaging x-ray, depending on the part of the body and on the imaging modality, is typically in the range of 0.1-10 mSv per image, but can be lowered using special imaging techniques, as for example x-ray phase contrast imaging or x-ray fluoroscopy. This actually limits the maximum number of radiography steps that can be taken. Being capable of performing a treatment session with just few radiation pulses using the radiation source having the parameters set by the present invention provides an additional advantage over the radio frequency accelerators. The system of the present invention thus can perform x-ray imaging of the target region at each radiation pulse.

In a preferred embodiment, the x-ray imaging system comprises an electron emitter, or cathode, which may be a wire undergoing a very high current, and an anode having a potential difference with respect to the cathode of at least 20 kV.

In another embodiment, the x-ray imaging system comprises a laser system for generating laser pulses focused on a solid, liquid, gaseous or plasma target.

In a preferred embodiment, the x-ray imaging system comprises an x-ray delivery system capable of shaping the x-ray beam both in fluence and spectrum; said x-ray delivery system may be a stack of metal foils.

In one preferred embodiment, the x-ray imaging system comprises a target position diagnostics, which may be a set of digital x-ray sensors connected with the control system. The target position diagnostics is preferably adapted to perform at least one of: x-ray absorption imaging, x-ray fluoroscopy imaging, x-ray phase contrast imaging.

In another embodiment, ballistic and snake photons medical imaging technique [1] system is used, capable of acquiring images with a time resolution lower than 200 ms.

In another embodiment, an imaging system based on detecting the Cerenkov radiation emitted by the radiation beam when it enters and exits the patient's body is used. This technique is very effective since the radiation is emitted in very short time ( $< 1$  ms).

In another embodiment, imaging system based on fluorescent markers is used. Such markers can be inserted into or near the target region and can be, for example, gold particles. The role of these markers is to either appear as a strong absorption object in the radiography, or to emit characteristic radiation once irradiated by the radiation pulse. These markers help in reducing the exposure time for the target region imaging.

Optionally, the imaging technologies, in particular MRI and x-ray imaging technologies, can be combined to get a more precise imaging. It is also preferable to combine any technique with fluorescent markers.

The imaging can be two-dimensional or three-dimensional.

The control system is capable of at least one of: processing the acquired x-ray image, calculating the changes to be applied to the treatment plan, and applying those changes to the x-ray machine, to the x-ray delivery system, and to the control system for the electron beam optimization.

- 5 The control system may include a control system for the electron beam optimization. The input and output of the control system for the electron beam optimization are connected with at least one component of the pulsed radiation source, for example with the laser plasma electron accelerator.

In a preferred embodiment of the device, the control system and/or the control system for the electron beam optimization is a computer.

- 10 The present invention also provides a method for testing and/or calibrating a system of the present invention, wherein a body of water (e.g., a water phantom) is irradiated by means of the pulsed radiation source by at least one pulse having the duration of less than 1 ms and depositing a dose corresponding to at least 50 mGy at a depth of at least 1 cm in water, and simultaneously the irradiated region is subjected to imaging by means of the imaging system within a time jitter shorter than 200 ms  
15 from the delivery of the irradiation pulse, wherein the imaging is carried out with a time resolution better than 200 ms, and the obtained image is used for calculating the deposited dose and optionally adjusting the system.

- The present invention further provides a method for radiotherapeutic treatment of a subject in need of such treatment using the system of the present invention, wherein the subject is irradiated by means of  
20 the pulsed radiation source by at least one pulse having the duration of less than 1 ms and depositing a dose corresponding to at least 50 mGy at a depth of at least 1 cm in water, and simultaneously the subject is subjected to imaging by means of the imaging system within a time jitter shorter than 200 ms from the delivery of the irradiation pulse, wherein the imaging is carried out with a time resolution better than 200 ms, and the obtained image is used for calculating the deposited dose and optionally  
25 adjusting the treatment.

- This method is advantageous over existing solutions since it allows for a precise reconstruction of the dose deposited into the target region and the patient's body. Moreover, it can be very effective in some specific cases like breast or lung tumor, where the target region is located in a fast moving region of the patient's body. In such cases this method helps in understanding how well the tumor was hit by the  
30 radiation pulse, and which fraction of the radiation has been delivered to the healthy tissue of the patient.

In a preferred embodiment, the imaging system comprises at least one pulsed x-ray imaging system and/or at least one MRI imaging unit.

In a preferred embodiment, the imaging system can monitor the target region via time-resolved 2-D or 3-D images.

In a preferred embodiment, gated radiotherapy technique is used for irradiation.

5 In a preferred embodiment, the imaging used is Cerenkov imaging to detect the in and out position of the radiation beam.

In a preferred embodiment, this method further comprises that after each radiation pulse, after few radiation pulses, or after the whole treatment session, the target region images are analyzed and the information about the position and, eventually, the shape of the target region are used in combination with the data relative to the radiation pulses to improve the treatment plan.

## 10 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 schematically illustrates one embodiment of the components of the device.

FIG. 2 schematically illustrates two different configuration embodiments for the laser transport.

FIG. 3 schematically illustrates one embodiment of the workflow of the control system of the device.

15 FIG. 4 schematically illustrates one embodiment of the pulsed radiation source, in the case of multiple radiation pulse arms, in particular with three radiation pulse arms.

FIG. 5 schematically illustrates one embodiment of the system with multiple radiation pulse arms mounted on robotic arms and multiple x-ray imaging modules mounted on static support, in particular with two radiation pulse arms and two x-ray imaging modules.

20 FIG. 6 schematically illustrates one embodiment of the system with MRI imaging system, x-ray imaging system and two radiation pulse arms, in particular with one radiation pulse arm implemented in the MRI imaging system.

FIG. 7 shows a 2-D plot of the dose deposited inside a 10x20 cm water phantom by one of the possible beams emitted by the pulsed radiation source.

## DETAILED DESCRIPTION OF THE INVENTION

25 Details of the present invention are further illustrated using the following exemplary embodiments. However, these examples should not be construed as limiting the scope of the claimed invention. Unless indicated otherwise, the embodiments shown in the figures are independent and may be used separately or in combination.

FIG. 1 schematically represents one possible embodiment of the system, in this specific case using x-ray imaging and a laser plasma electron accelerator. The synchronization system **101** synchronizes, with a time jitter lower than 200 ms, the emission of an x-ray pulse from the x-ray machine **107** and the emission of a laser pulse from the laser system **102**. The laser pulse is transported through the laser transport **103**, and then focused by the laser focusing system **104** into the plasma electron accelerator **105**. Each single electron beam generated in the plasma electron accelerator **105** goes into the radiation beam delivery system **106**, which operates on each electron pulse and sends to the target **110** a radiation pulse. The radiation beam delivery system **106** can check the electron beam quality and can stop or modify the beam in order to meet the requirements set by the treatment plan. The radiation beam delivery system **106** may also use the kinetic energy of the electron beam to create a different particle beam, for example a beam of high energy photons, positrons, neutrons or pi mesons. For this reason, the radiation pulse sent to the target by the radiation beam delivery system **106** is not restricted to be an electron beam, but could also be, for example, a high energy photon beam, a positron beam, a neutron beam, a pi meson beam, or a beam containing a mixture of these particles. While the radiation pulse hits the target **110**, the x-ray pulse coming from the x-ray machine **107**, and shaped by the x-ray delivery system **108**, hits the target **110** within a time window shorter than 200 ms. The target position diagnostics **109** detect the x-ray signal coming from the x-ray delivery system **108**, after it passes through the target **110**.

In a preferred embodiment, the synchronization system **101** is an electrical device capable of sending electrical pulses synchronized with a tunable delay with a time resolution better than 200 ms.

In a preferred embodiment, the laser system **102** is a Ti:Sa laser, delivering laser pulses with energy of at least 100 mJ and pulse duration shorter than 1  $\mu$ s.

In another embodiment, the laser system **102** is a Ti:Sa laser, pumped by diode pumped solid state lasers with frequency conversion, delivering laser pulses with energy of at least 100 mJ and pulse duration shorter than 1  $\mu$ s.

In a preferred embodiment, as schematically illustrated in FIG. 2 (a), the laser transport **103** comprises the compressor **202**, which compresses the laser pulse in time to less than 100 fs, and the transport **203**, which is an optical transport line that sends the laser pulse to the laser focusing system **104**.

In another embodiment, as schematically illustrated in FIG. 2 (b), the laser transport **103** comprises a phased optical fiber array **201**, which transports the uncompressed laser pulse, which has a time duration of at least 10 ps, to the compressor **202**. The compressor **202** compresses the laser pulse in time to less than 100 fs and then it sends the laser pulse to the transport **203**, which is an optical transport line that sends the laser pulse to the laser focusing system **104**.

In a preferred embodiment, the laser focusing system **104** is an optical system that focuses the laser pulse inside the plasma electron accelerator **105**, comprising at least one positioning mirror and at least one off-axis parabola capable of focusing the laser pulse to an intensity higher than  $10^{12}$  W/cm<sup>2</sup>.

5 In a preferred embodiment, the laser focusing system **104** is an optical system that focuses the laser pulse inside the plasma electron accelerator **105**, comprising at least one positioning mirror and at least one spherical mirror capable of focusing the laser pulse to an intensity higher than  $10^{12}$  W/cm<sup>2</sup>.

In a preferred embodiment, the plasma electron accelerator **105** is a device comprising at least one gas target mounted on a remotely controlled motorized stage with at least one degree of freedom to align the gas target according to the laser focus.

10 In a preferred embodiment, the radiation beam delivery system **106** is a device comprising at least one of the following components: a magnetic field to select the energy of the electron beam and to eventually shape the electron beam, a beam charge diagnostic, a magnetic system to change the size of the electron beam, and eventually focus or defocus it, and a solid target to change the beam divergence and/or to generate other particle beams, for example high energy photons (x-ray and gamma-ray),  
15 positrons, neutrons or pi mesons.

In a preferred embodiment, the x-ray machine **107** is a device comprising an electron emitter, or cathode, which may be a wire undergoing a current higher than 1  $\mu$ A, and an anode having a potential difference with respect to the cathode of at least 20 kV.

20 In another embodiment, the x-ray machine **107** is a device comprising laser pulses that can come from the laser system **102** or from an independent laser system, focused on a solid, liquid, gaseous or plasma target.

In a preferred embodiment, the x-ray delivery system **108**, is a device capable of shaping the x-ray beam fluence and/or spectrum, which may be a stack of metal foils.

25 In a preferred embodiment, the target position diagnostics **109** may be a set of digital x-ray sensors connected with the control system **301**. The control system **301** is capable of doing, at each irradiation step, at least one of the following: processing the acquired x-ray image, calculating the changes to be applied to the treatment plan, and applying those changes to the x-ray machine **107**, to the x-ray delivery system **108**, and to the control system for the electron beam optimization **306**.

30 In a preferred embodiment, the target position diagnostics **109** can be set to perform x-ray absorption imaging, x-ray fluoroscopy imaging or x-ray phase contrast imaging.

The system may contain a control system for the electron beam optimization **306**. In the following, the input and output of the control system for the electron beam optimization **306** are connected with some

sub-parts of the laser plasma electron accelerator, but they can be connected to different sub-parts of the laser plasma electron accelerator, as well known to those skilled in the art.

Each laser pulse, originated in the laser system **102**, and passing through the laser transport **103**, the laser focusing system **104** and the plasma electron accelerator **105**, can be monitored by several

5 diagnostics. Among these diagnostics there is at least one of the following: the spectral shape diagnostic, which measures the spectral shape of the laser pulse; the energy diagnostic, which measures the energy of the laser pulse; the beam shape diagnostic, which measures the energy distribution of the laser pulse along its transverse section; the spectral phase diagnostic, which measures the spectral phase of the laser pulse; the temporal profile diagnostic, which measures the

10 temporal profile of the laser pulse; the laser focal spot diagnostic, which measures the spatial distribution of the laser pulse in its focus; and the wavefront diagnostic, which measures the phase front of the laser pulse. The gas target that emits the electron pulses can be monitored by several diagnostics. Among these diagnostics there is at least one of the following: the plasma diagnostic, which measures the plasma density inside the target; the laser plasma coupling diagnostic, which

15 measures the coupling in the laser plasma interaction; and the laser propagation diagnostic, which measures the laser propagation after the plasma. The electron pulses accelerated by the plasma electron accelerator **105** can be monitored by several diagnostics. Among these diagnostics, there is at least one of the following: the electron beam shape diagnostic, which measures the transverse shape of the electron pulse; the electron beam charge diagnostic, which measures the charge of the electron

20 pulse; the electron beam spectral shape diagnostic, which measures the spectral shape of the electron pulse; the beam divergence diagnostic, which measures the divergence of the electron pulse; and the beam temporal profile diagnostic, which measures the temporal profile of the electron pulse. The data acquired by the diagnostics are sent to the control system for the electron beam optimization **306**, which analyzes them and, eventually, saves the results. In the case the electron beam is not satisfying

25 the parameters required for the treatment, the control system for the electron beam optimization **306** modifies the state of some components until the electron beam reaches the parameters desired. The control system for the electron beam optimization **306** operates on at least one of the following components: the spectral shaping device, to modify the spectral shape of the laser pulses; the energy attenuator, to change the energy of the laser pulses; the spectral phase shaper, to modify the spectral

30 phase of the laser pulses; the compressor gratings motors, to change the duration and/or the temporal profile of the laser pulses; the positioning motors, to modify the path of the laser pulses in the laser focusing system **104**; the focusing optics motors, to modify the position and the shape of the laser focal spot; the gas density shaper, to modify the density profile of the gas target; the gas target motors, to change the position of the gas target within the plasma electron accelerator **105**; the adaptive optics,

35 to modify the wavefront of the laser pulse, and so the shape of the focal spot; the radiation spectrum fine shaper, which modifies the spectrum of the radiation pulse; the radiation pulse particle number

controller, which adjusts the number of particles in the radiation pulse; the radiation pulse spatial distribution shaper, which modifies the spatial distribution of the radiation pulse; the radiation pulse divergence controller, which adjusts the divergence of the radiation pulse; and the radiation pulse temporal profile controller, which adjusts the duration and/or the temporal profile of the radiation pulse.

In a preferred embodiment, the control system for the electron beam optimization 306 is a computer.

In a preferred embodiment, the spectral shape diagnostic can be an optical and infrared light spectrometer.

In a preferred embodiment, the spectral shaping device is a mazzler.

10 In another embodiment, the spectral shaping device comprises at least one colored optical filter.

In another embodiment, the spectral shaping device comprises at least one prism and at least one neutral optical filter.

In a preferred embodiment, the energy diagnostic is a calorimeter.

In another embodiment, the energy diagnostic comprises at least one optical diode.

15 In a preferred embodiment, the energy attenuator comprises at least one half-lambda plate and at least one polarizer.

In a preferred embodiment, the beam shape diagnostics comprises a set of mask filters.

In another embodiment, the beam shape diagnostics comprises a camera and imaging optics.

20 In a preferred embodiment, the spectral phase diagnostic comprises at least one of the following devices: SPIDER, FROG, D-SCAN and GRENOUILLE.

In a preferred embodiment, the spectral phase shaper is a dazzler.

In a preferred embodiment, the adaptive optics comprise a deformable mirror.

In a preferred embodiment, the temporal profile diagnostic comprises at least one of the following devices: SPIDER, FROG, D-SCAN and GRENOUILLE.

25 In a preferred embodiment, the compressor gratings motors comprise at least one linear stage mounted below one of the gratings to change the optical path of different wavelengths.

In another embodiment, the compressor grating motors comprise at least one rotative stage mounted below one of the gratings to change the optical path of different wavelengths.



In a preferred embodiment, the positioning motors comprise at least one actuator mounted on at least one mirror mount capable of moving with at least one degree of freedom the at least one positioning mirror.

5 In a preferred embodiment, the focusing optics motors comprise at most five rotation stages and at most seven linear stages mounted below the focusing optics, capable of moving the focusing optics with at least one degree of freedom.

In a preferred embodiment, the electron beam shape diagnostic comprises at least one fluorescent screen coupled with a CCD.

10 In a preferred embodiment, the electron beam charge diagnostic comprises at least one Integrating Current Transformer.

In another embodiment, the electron beam charge diagnostic comprises at least one fluorescent screen coupled with a CCD.

In a preferred embodiment, the electron beam spectral shape diagnostic is a device which comprises at least one magnetic dipole and at least one fluorescent screen coupled with a CCD.

15 In a preferred embodiment, the laser focal spot diagnostic comprises a CCD and a reflective object.

In a preferred embodiment, the plasma diagnostic comprises at least one CCD with imaging optics looking at the gas target.

20 In a preferred embodiment, the gas density shaper is a device capable of changing the spatial density of the gas target, comprising at least one of the following components: a gas pressure regulator, a gas mixture regulator, and at least one wire and/or at least one sharp edge, remotely controlled and eventually automatic, that modifies the trajectory of the supersonic gas jet, thus changing the plasma density profile.

In a preferred embodiment, the gas target motors are a set of at least one linear stage capable of moving the gas target with at least one degree of freedom.

25 In a preferred embodiment, the wavefront diagnostic comprises a wavefront sensor.

In a preferred embodiment, the laser propagation diagnostic comprises a CCD looking at the laser exiting the target.

In a preferred embodiment, the laser plasma coupling diagnostic comprises a CCD with imaging optics looking at the light emitted by the target.

In a preferred embodiment, the beam divergence diagnostic comprises at least one fluorescent screen coupled with a CCD.

In a preferred embodiment, the beam temporal profile diagnostic comprises a streak camera with a resolution better than 10 ps.

- 5 In another embodiment, the beam temporal profile diagnostic comprises an infrared spectrometer and a metallic target.

In a preferred embodiment, the radiation spectrum fine shaper comprises at least one magnetic field and at least one slit.

- 10 In a preferred embodiment, the radiation pulse particle number controller comprises at least one magnetic field and at least one slit.

In another embodiment, the radiation pulse particle number controller comprises at least one solid target and at least one slit.

In a preferred embodiment, the radiation pulse spatial distribution shaper comprises at least one solid target.

- 15 In a preferred embodiment, the radiation pulse divergence controller comprises at least one magnetic field and at least one slit.

In another embodiment, the radiation pulse divergence controller comprises at least one solid target. In a preferred embodiment, the radiation pulse temporal profile controller comprises at least one magnetic field.

- 20 In another embodiment, the radiation pulse temporal profile controller comprises at least one solid target.

In a preferred embodiment, the device is controlled by a wireless device, for example a tablet or a laptop.

- FIG. 3 schematically illustrates one embodiment of the control system of the device, in the case of a laser plasma electron accelerator as a pulsed radiation source and a generic imaging system. The control system 301 receives from the imaging system 302 the data containing information on the position and, eventually, the shape of the target region. The control system 301 elaborates the data received and creates a geometry reconstruction 303 to locate the target region in a 2D or 3D coordinate system. If the data coming from the imaging system 302 are not accurate enough for the geometry reconstruction, the control system 301 can operate on the imaging system 302 in order to get more accurate imaging data. Then, using the data concerning the radiation pulse coming from at least
- 25
- 30

one among the radiation beam delivery system **106**, the plasma electron accelerator **105**, and the control system for the electron beam optimization **306**; the control system **301** creates a map of the dose deposited into the patient's body and into the target region **304** using the same 2D or 3D coordinate system. After, the control system **301** compares the map of the dose deposited into the patient's body and into the target region **304** with the predicted dose deposited map, and eventually creates a modified treatment plan **305**. After, the control system **301** operates on the control system for the electron beam optimization **306** and/or on the radiation beam delivery system **106**, to meet the requirements for the subsequent radiation pulse to be delivered according to the current treatment plan.

FIG. 4 schematically illustrates one possible embodiment of the pulsed radiation source, in the case of multiple radiation pulse arms, in particular with three radiation pulse arms. In this case, each of the three arms is a laser plasma electron accelerator.

The laser master oscillator **401** sends fs, nJ pulses at a MHz repetition rate to the booster **402**, where the energy is increased at least to the  $\mu$ J level and the repetition rate lowered to the kHz level. Then the laser pulses are sent to the stretcher **403**, where they are elongated in time to at least 10 ps. After they are sent to the first amplifier **404**, which delivers laser pulses at a frequency of at least 5 Hz and with an energy of at least few mJ to the laser pulse delivery system **405**. The laser pulse delivery system **405** can either stop the laser pulses or deliver each of them to the first radiation pulse arm **421**, or to the second radiation pulse arm **422**, or to the third radiation pulse arm **423**. All the radiation pulse arms in this scheme are equivalent. The final amplifier **406**, **407**, **408** receives the laser pulses coming from the laser pulse delivery system **405**, amplifies them to at least 100 mJ and then sends them to the laser transport **409**, **410**, **411**. The laser transport **409**, **410**, **411** compresses the laser pulses in time into the 20-200 fs range and sends them to the laser focusing system **412**, **413**, **414**, which focuses the laser pulses into the plasma electron accelerator **415**, **416**, **417**. The plasma electron accelerator **415**, **416**, **417** uses the laser pulses to accelerate the electron pulses, and sends these last to the radiation beam delivery system **418**, **419**, **420**, where each radiation pulse can be controlled, modified and eventually blocked.

In the following, at least one possible realization of each component disclosed in FIG. 4 is disclosed.

In a preferred embodiment, the laser master oscillator **401** is a Ti:Sa oscillator.

In a preferred embodiment, the booster **402** comprises a laser pulse amplifier, for example a regenerative amplifier or a multi-pass amplifier.

In a preferred embodiment, the stretcher **403** is an optical device comprising at least one pair of diffractive gratings.

In a preferred embodiment, the 1<sup>st</sup> amplifier **404** comprises a Ti:Sa crystal pumped by a diode pumped solid state laser with frequency conversion.

In another embodiment, the 1<sup>st</sup> amplifier **404** comprises a Ti:Sa crystal pumped by a flash lamp pumped solid state laser with frequency conversion.

- 5 In a preferred embodiment, the laser pulse delivery system **405** is an optical system composed by a set of fast flip mirrors.

In another embodiment, the laser pulse delivery system **405** is a fast rotating mirror.

In another embodiment, the laser pulse delivery system **405** comprises at least one galvo mirror.

- 10 In a preferred embodiment, the final amplifiers **406**, **407** and **408** comprise Ti:Sa crystals pumped by diode pumped solid state lasers with frequency conversion.

In a another embodiment, the final amplifiers **406**, **407** and **408** comprise Ti:Sa crystals pumped by flash lamp pumped solid state laser with frequency conversion.

- 15 FIG. **5** schematically illustrates one exemplary embodiment of the system with multiple radiation pulse arms mounted on robotic arms and multiple imaging modules mounted on static supports, in particular with two laser plasma electron accelerators and two x-ray imaging modules. The laser pulse delivery system located on the common laser table **501** sends selectively the laser pulses to the final amplifier tables **502** or **503**. The amplified laser pulses are then sent to the radiation stations **504** or **505**. The radiation stations send their radiation pulses to the patient lying on the treatment bed **509**; at the same time the x-ray sources **506** and **507**, triggered by the synchronization system, irradiate the target region. The x-ray detector **508** and another x-ray sensor located inside the treatment bed **509** collect the attenuated x-ray and send these data to the control system **301**.

In a preferred embodiment of the device, the common laser table **501** comprises at least one laser master oscillator, at least one booster, at least one stretcher, at least one first amplifier, and at least one laser pulse delivery system.

- 25 In a preferred embodiment of the device, the radiation stations **504** and **505** are devices fixed to the ground, to a wall or to the ceiling of the treatment room.

In a preferred embodiment, each of the radiation stations **504** and **505** comprises a laser transport, a laser focusing system, a plasma electron accelerator, and a radiation beam delivery system.

- 30 In a preferred embodiment, at least one of the radiation stations **504** and **505** comprises a laser transport comprising a phased optical fiber array.

In a preferred embodiment, at least one of the radiation stations **504** and **505** comprises a robotic arm or a gantry capable of moving the plasma electron accelerator.

In another embodiment, at least one of the radiation stations **504** and **505** comprises a robotic arm or a gantry capable of moving the radiation beam delivery system.

- 5 In another embodiment, at least one of the radiation stations **504** and **505** comprises a robotic arm or a gantry capable of moving both the plasma electron accelerator and the radiation beam delivery system.

In another embodiment, at least one of the radiation stations **504** and **505** comprises a robotic arm or a gantry capable of moving the compressor, the transport, the laser focusing system, the plasma electron accelerator and the radiation beam delivery system.

- 10 In a preferred embodiment of the device, the x-ray sources **506** and **507** are devices comprising at least one x-ray machine and at least one x-ray delivery system.

In a preferred embodiment of the device, at least one of the x-ray sources **506** and **507** comprises a robotic arm or a gantry capable of moving at least one x-ray machine and at least one x-ray delivery system.

- 15 In a preferred embodiment of the device, the x-ray detector **508** comprises at least one fluorescent screen coupled with a CCD.

In another embodiment of the device, the x-ray detector **508** comprises at least one digital x-ray detector.

- 20 In a preferred embodiment of the device, the treatment bed **509** is a stable bed movable along at least one direction.

In a preferred embodiment of the device, the treatment bed **509** has an x-ray detector **508** integrated.

- 25 FIG. 6 schematically illustrates an exemplary embodiment of the device with a combination of different imaging systems and multiple radiation pulse arms; in particular with one MRI imaging system, one x-ray imaging system, and two radiation pulse arms. The radiation pulse arm **602** is implemented into the MRI imaging system **601**. The radiation pulse arm **603** is stand-alone and pointing toward the patient, that is laying on the treatment bed **604**. The x-ray source **605** is pointed toward the patient and the x-ray detector **606** collects the x-ray passing through the patient.

In a preferred embodiment, the MRI imaging system **601** is capable of imaging the target region with a time resolution better than 200 ms.

In a preferred embodiment, the radiation pulse arm implemented into the MRI 602 is a laser plasma electron accelerator emitting neutral radiation.

In a preferred embodiment, the radiation pulse arm 603 can be mounted on a static support, on a mechanically movable support, on a robotic arm, or on a gantry.

- 5 In a preferred embodiment of the device, the MRI imaging system 601, the radiation pulse arm 602, the radiation pulse arm 603 and the x-ray imaging system 605 are synchronized by a common synchronization system with a time resolution better than 200 ms.

In a preferred embodiment of the device, the treatment bed 604 may have an x-ray sensor incorporated.

- 10 In another embodiment of the device, the treatment bed 604 can move along at least one direction.

In a preferred embodiment of the device, the x-ray detector 606 can be set to perform x-ray absorption imaging, x-ray fluoroscopy imaging or x-ray phase contrast imaging.

- FIG. 7 shows a 2-D plot describing the dose deposited inside a 10x20 cm water phantom by one of the possible beams emitted by the pulsed radiation source described in this patent application. In particular, it shows a beam containing 80 pC of electrons with 100 MeV kinetic energy. As it can be observed, a single radiation pulse of this kind can deposit a dose higher than 50 mGy at a depth of at least 1 cm in water.
- 15

## REFERENCES

- [1] S. Farsiu et al., "Statistical detection and imaging of objects hidden in turbid media using ballistic photons", Applied Optics, Vol. 46 No. 23 (2007)
- 20

1. A method for testing and/or calibrating a system for radiotherapy, wherein a body of water is irradiated by means of the pulsed radiation source by at least one pulse having the duration of less than 1 ms and depositing a dose corresponding to at least 50 mGy at a depth of at least 1 cm in water, and simultaneously the irradiated region is subjected to imaging by means of the imaging system within a time jitter shorter than 200 ms from the delivery of the irradiation pulse, wherein the imaging is carried out with a time resolution better than 200 ms, and the obtained image is used for calculating the deposited dose and optionally adjusting the system.
2. A system for radiotherapy which comprises at least one pulsed radiation source for delivering radiation pulses shorter than 1 ms, at least one imaging system, at least one control system for determining the deposited dose, and at least one synchronization system for synchronizing said pulsed radiation source and said imaging system within a time jitter shorter than 200 ms, wherein said pulsed radiation source is capable of delivering a dose of at least 50 mGy at a depth of at least 1 cm in water within 1 ms, wherein said imaging system has the time resolution better than 200 ms, and wherein said control system is connected to the pulsed radiation source and to the imaging system.
3. The system according to claim 2, wherein the pulsed radiation source has to be selected from the group comprising: sources of electron beams, sources of high energy photon beams, sources of positron beams, sources of neutron beams, sources of pi meson beams, sources of beams comprising combinations of these particles.
4. The system according to any one of claims 2 to 3, wherein the pulsed radiation source may comprise a ultra-fast laser system, a laser transport system, a laser focusing system, a laser plasma electron accelerator, a radiation beam delivery system.
5. The system according to any one of claims 2 to 4, wherein the ultra-fast laser system is a Ti:Sa laser system, a diode pumped solid state laser system or a phased optical fiber array laser system; said ultra-fast laser system being pumped by a diode laser, by a diode pumped solid state laser with frequency conversion, by a flash lamp pumped solid state laser with frequency conversion, or by a combination of these systems.
6. The system according to any one of claims 2 to 5, wherein the control system is capable, after each irradiation step of at least one of the following: processing the acquired image, calculating the changes to be applied to the treatment plan, operating on the imaging system, and operating on the pulsed radiation source.
7. The system according to any one of claims 2 to 6, wherein the pulsed radiation source comprises at least one laser beam diagnostic, selected from: a spectral shape diagnostic for measuring the spectral

shape of the laser pulse; an energy diagnostic for measuring the energy of the laser pulse; a beam shape diagnostic for measuring the energy distribution of the laser pulse along its transverse section; a spectral phase diagnostic for measuring the spectral phase of the laser pulse; a temporal profile diagnostic for measuring the temporal profile of the laser pulse; a laser focal spot diagnostic for measuring the spatial distribution of the laser pulse in its focus; and a wavefront diagnostic for measuring the phase front of the laser pulse.

8. The system according to any one of claims 2 to 7, wherein the pulsed radiation source comprises a gas target for emitting the electron pulses, which can optionally be monitored by one or more diagnostics selected from: a plasma diagnostic for measuring the plasma density inside the target; a laser plasma coupling diagnostic for measuring the coupling in the laser plasma interaction; and a laser propagation diagnostic for measuring the laser propagation after the plasma.

9. The system according to any one of claims 2 to 8, wherein the pulsed radiation source comprises one or more diagnostics selected from: an electron beam shape diagnostic for measuring the transverse shape of the electron pulse; a beam charge diagnostic for measuring the charge of the electron pulse; an electron beam spectral shape diagnostic for measuring the spectral shape of the electron pulse; a beam divergence diagnostic for measuring the divergence of the electron pulse; and a beam temporal profile diagnostic for measuring the temporal profile of the electron pulse.

10. The system according to any one of claims 2 to 9, wherein the pulsed radiation source comprises a control system for the electron beam optimization for collecting the data from all diagnostics, analyzing said data, optionally for modifying the state of one or more components of the pulsed radiation source, and optionally for saving the results.

11. The system according to any one of claims 2 to 10, wherein the pulsed radiation source comprises at least one of the following components: a spectral shaping device for modifying the spectral shape of the laser pulse; an energy attenuator for changing the energy of the laser pulse; a spectral phase shaper for modifying the spectral phase of the laser pulse; compressor gratings motors for changing the duration and/or the temporal profile of the laser pulse; positioning motors for modifying the path of the laser pulse in the laser focusing system; focusing optics motors for modifying the position and the shape of the laser focal spot; a gas density shaper for modifying the density profile of the gas target; gas target motors for changing the position of the gas target within the plasma electron accelerator; adaptive optics for modifying the wavefront of the laser pulse and so the shape of the focal spot; a radiation spectrum fine shaper for modifying the spectrum of the radiation pulse; a radiation pulse particle number controller for adjusting the number of particles in the radiation pulse; a radiation pulse spatial distribution shaper for modifying the spatial distribution of the radiation pulse; a radiation pulse divergence controller for adjusting the divergence of the radiation pulse; and a radiation pulse temporal profile controller for adjusting the temporal profile of the radiation pulse.



12. The system according to any one of claims 2 to 11, wherein the pulsed radiation source comprises a laser master oscillator, a booster, a stretcher, a first amplifier, a laser pulse delivery system, and one or more pulsed radiation arms; wherein each said pulsed radiation arm comprises a final amplifier, a laser transport system, a laser focusing system, a laser plasma electron accelerator, a radiation beam delivery system.
13. The system according to any one of claims 2 to 12, wherein the imaging system is based on pulsed x-ray imaging technology, or magnetic resonance imaging (MRI) technology, or ballistic and snake photon technology, or fluorescent markers, or Cerenkov radiation detection, or a combination of any two or more of these technologies.
14. The system according to any of claims 2 to 13, wherein the imaging system comprises at least one of the following: a laser system pointing on the target region and a gated detector; a real time magnetic imaging device; a laser system and at least one laser delivery system capable of focusing the laser pulses at an intensity higher than  $10^{10}$  W/cm<sup>2</sup> on a solid, liquid gaseous or plasma target; a device comprising an electron emitter, or cathode, which may be a wire undergoing a current higher than 1  $\mu$ A, an anode having a potential difference with respect to the cathode of at least 20 kV, an x-ray delivery system and an x-ray detector; an x-ray source capable of performing x-ray phase contrast imaging.
15. The system according to any of claims 2 to 14, wherein the synchronization system comprises at least one ultra-fast laser system shared with the imaging system and with the pulsed radiation source.
16. The system according to any one of claims 2 to 15, comprising a control system for the electron beam optimization, wherein the input and output of said control system for the electron beam optimization are connected with at least one component of the pulsed radiation source, preferably with the laser plasma electron accelerator.
17. The system according to any of claims 2 to 16, wherein at least one pulsed radiation source and/or at least one imaging system, is mounted on a static or a movable support, preferably a gantry or a robotic arm.
18. The system according to any one of claims 2 to 17, wherein the laser transport system comprises a phased optical fiber array that brings the uncompressed laser pulses from the last laser amplifier to the compressor.
19. A method for radiotherapeutic treatment of a subject in need of such treatment using the system of any one of claims 2 to 18, wherein the subject is irradiated by means of the pulsed radiation source by at least one pulse having the duration of less than 1 ms and depositing a dose corresponding to at least 50 mGy at a depth of at least 1 cm in water, and simultaneously the subject is subjected to imaging by

means of the imaging system within a time jitter shorter than 200 ms from the delivery of the irradiation pulse, wherein the imaging is carried out with a time resolution better than 200 ms, and the obtained image is used for calculating the deposited dose and optionally adjusting the treatment.

20. The method according to claim 19, which further comprises that after each radiation pulse, after  
5 few radiation pulses, or after the whole treatment session, the target region images are analyzed and the information on the position and, eventually, the shape of the target region are used, in combination with the data relative to the radiation pulses, to calculate the dose deposited into the target region and into the healthy tissue, and to improve the treatment plan.

REVENDICATIONS

93102

1. Procédé pour tester et/ou calibrer un système pour la radiothérapie, où un plan d'eau est illuminé au moyen de la source de radiation pulsée par au moins une impulsion ayant la durée de moins de 1 ms et le dépôt d'une dose correspondant à au moins 50 mGy à une profondeur d'au moins 1 cm dans l'eau et simultanément la région illuminée est soumise à l'image au moyen du système d'image dans une vibration de temps plus court que 200 ms de la livraison de l'impulsion d'irradiation, où l'image est effectuée avec une résolution de temps mieux que 200 ms et l'image obtenue est utilisée pour calculer la dose déposée et ajuster facultativement le système.
2. Un système pour la radiothérapie qui comprend au moins une source de radiation pulsée de livrer des impulsions de radiation plus court que 1 ms, au moins un système d'image, au moins un système de commande pour déterminer la dose déposée et au moins un système de synchronisation pour synchroniser ladite source de radiation pulsée et ledit système d'image dans une vibration de temps plus court que 200 ms, dans laquelle la source de radiation pulsée est capable de livrer une dose d'au moins 50 mGy à une profondeur d'au moins 1 cm dans l'eau dans 1 ms, dans lequel le système d'image a la résolution de temps mieux que 200 ms et a où ledit système de commande est connecté à la source de radiation pulsée et au système d'image.
3. Système selon la revendication 2, où la source de radiation pulsée doit être choisi parmi le groupe comprenant : les sources de faisceaux électroniques, les sources de hauts rayons de photon d'énergie, les sources de rayons de positron, les sources de rayons à neutrons, les sources de rayons de méson pi, les sources de rayons comprenant les combinaisons de ces particules.
4. Système selon l'une quelconque des revendications 2 à 3, où la source de radiation pulsée peut comprendre un système laser ultra-rapide, un système laser de transport, un système de focalisation de laser, un accélérateur électronique plasma laser, un système de livraison de rayon de radiation.
5. Système selon l'une quelconque des revendications 2 à 4, où le système laser ultra-rapide est un système laser Ti:Sa, une diode le système de laser de solide pompé ou une fibre optique de phase rangent le système laser; le système laser ultra-rapide étant pompé par un laser de diode, par une diode pompée avec un laser à l'état solide avec la conversion de fréquence, par une lampe de flash pompée avec un laser à l'état solide avec la conversion de fréquence, ou par une combinaison de ces systèmes.

6. Système selon l'une quelconque des revendications 2 à 5, où le système de commande est capable, après chaque étape d'irradiation, de faire au moins une parmi les choses suivantes: traiter l'image acquise, calculer les changements à être appliqué au plan de traitement, opérer sur le système d'image et le fonctionnement sur la source de radiation pulsée.
- 5 7. Système selon l'une quelconque des revendications 2 à 6, où la source de radiation pulsée comprend au moins un rayon laser diagnostique, choisi parmi: une forme spectrale diagnostique pour mesurer la forme spectrale de l'impulsion laser; une énergie diagnostique pour mesurer l'énergie de l'impulsion laser; une forme de rayon diagnostique pour mesurer la distribution d'énergie de l'impulsion laser le long de sa section transversale; une phase spectrale diagnostique pour mesurer la phase spectrale de l'impulsion laser; un profil temporel diagnostique pour mesurer le profil temporel de l'impulsion laser; une tache focale laser diagnostique pour mesurer la distribution spatiale de l'impulsion laser dans son foyer; et un front des ondes diagnostique pour mesurer le front de phase de l'impulsion laser.
- 10 8. Système selon l'une quelconque des revendications 2 à 7, où la source de radiation pulsée comprend une cible à gaz pour émettre les impulsions électroniques, qui peuvent facultativement être contrôlées par un ou plusieurs diagnostic choisi parmi : un plasma diagnostique pour mesurer la densité plasma à l'intérieur de la cible; un accouplement plasma laser diagnostique pour mesurer l'accouplement dans l'interaction plasma laser; et une propagation laser diagnostique pour mesurer la propagation laser après le plasma.
- 15 9. Système selon l'une quelconque des revendications 2 à 8, où la source de radiation pulsée comprend un ou plusieurs diagnostic choisi parmi : une forme de faisceau électronique diagnostique pour mesurer la forme transversale de l'impulsion électronique; une charge de rayon diagnostique pour mesurer la charge de l'impulsion électronique; un faisceau électronique la forme spectrale diagnostique pour mesurer la forme spectrale de l'impulsion électronique; une divergence de rayon diagnostique pour mesurer la divergence de l'impulsion électronique; et un rayon le profil temporel diagnostique pour mesurer le profil temporel de l'impulsion électronique.
- 20 10. Système selon l'une quelconque des revendications 2 à 9, où la source de radiation pulsée comprend un système de commande pour l'optimisation de faisceau électronique pour rassembler les données de tout le diagnostic, analysant des données dites, facultativement pour modifier l'état d'un ou plusieurs composants de la source de radiation pulsée et facultativement pour sauver les résultats.
- 25 11. Système selon l'une quelconque des revendications 2 à 10, où la source de radiation pulsée comprend au moins un des composants suivants : un dispositif de formation spectral
- 30

pour modifier la forme spectrale de l'impulsion laser; un atténuateur d'énergie pour changer l'énergie de l'impulsion laser; une phase spectrale formatrice pour modifier la phase spectrale de l'impulsion laser; des moteurs de rôpages de compresseur pour changer la durée et/ou le profil temporel de l'impulsion laser; le positionnement de moteurs pour modifier le chemin de l'impulsion laser dans le système de focalisation de laser; la focalisation de moteurs d'optique pour modifier la position et la forme de la tache focale laser; une densité à gaz formatrice pour modifier le profil de densité de la cible à gaz; des moteurs cibles à gaz pour changer la position de la cible à gaz dans l'accélérateur d'électron plasma ; l'optique adaptative pour modifier le front des ondes de l'impulsion laser et ainsi la forme de la tache focale; une amende de spectre de radiation formatrice pour modifier le spectre de l'impulsion de radiation; une particule d'impulsion de radiation numérote le contrôleur pour ajuster le nombre de particules dans l'impulsion de radiation; une impulsion de radiation la distribution spatiale formatrice pour modifier la distribution spatiale de l'impulsion de radiation; un contrôleur de divergence d'impulsion de radiation pour ajuster la divergence de l'impulsion de radiation; et une impulsion de radiation le contrôleur de profil temporel pour ajuster le profil temporel de l'impulsion de radiation.

12. Système selon l'une quelconque des revendications 2 à 11, où la source de radiation pulsée comprend un oscillateur de maître laser, un booster, une civière, un premier amplificateur, un système de livraison d'impulsion laser et un ou des bras de radiation plus pulsés; où ledit bras de radiation pulsé comprend un amplificateur final, un système laser de transport, un système de focalisation de laser, un accélérateur électronique plasma laser, un système de livraison de rayon de radiation.

13. Système selon l'une quelconque des revendications 2 à 12, où le système d'image est basé sur la technologie d'imagerie radiographique pulsée, ou la technologie de l'imagerie par résonance magnétique (IRM), ou la balistique et la technologie de photon de serpent, ou des marqueurs fluorescents, ou la détection de radiation Cerenkov, ou une combinaison de deux ou plusieurs de ces technologies.

14. Système selon l'une quelconque des revendications 2 à 13, où le système d'image comprend au moins une chose suivante: un système laser indiquant sur la région cible et un détecteur clôturé; un dispositif d'image temps réel magnétique; un système laser et au moins un système de livraison laser capable de concentrer les impulsions laser à une intensité plus haut que  $10^{10}$  W/cm<sup>2</sup> sur une cible gazeuse ou plasma solide, liquide; un dispositif comprenant un émetteur électronique, ou une cathode, qui peut être un fil subissant un courant plus haut que 1  $\mu$ A, une anode ayant une différence potentielle en ce qui concerne la cathode

d'au moins 20 kV, un système de livraison radiographique et un détecteur radiographique; une source radiographique capable d'image contrasté de phase radiographique performante.

15. Système selon l'une quelconque des revendications 2 à 14, où le système de synchronisation comprend au moins un système laser ultra-rapide partagé avec le système d'image et avec la source de radiation pulsée.

16. Système selon l'une quelconque des revendications 2 à 15, comprenant un système de commande pour l'optimisation de faisceau électronique, où l'apport et la production de système de commande dit pour l'optimisation de faisceau électronique est connecté avec au moins un composant de la source de radiation pulsée, de préférence avec l'accélérateur électronique plasma laser.

17. Système selon l'une quelconque des revendications 2 à 16, où au moins une source de radiation pulsée et/ou au moins un système d'image, est monté sur un statique ou un support mobile, de préférence un portique ou un bras robotisé.

18. Système selon l'une quelconque des revendications 2 à 17, où le système laser de transport comprend un tableau de fibre optique de phase qui apporte les impulsions laser non compressées du dernier amplificateur laser au compresseur.

19. Méthode pour le traitement radio-thérapeutique d'un sujet dans le besoin d'un tel traitement utilisant le système de l'une quelconque des revendications 2 à 18, où le sujet est illuminé au moyen de la source de radiation pulsée par au moins une impulsion ayant la durée de moins de 1 ms et le versement d'une dose correspondant à au moins 50 mGy à une profondeur d'au moins 1 cm dans l'eau et simultanément le sujet est soumis à l'image au moyen du système d'image dans une vibration de temps plus court que 200 ms de la livraison de l'impulsion d'irradiation, où l'image est effectuée avec une résolution de temps mieux que 200 ms et l'image obtenue est utilisée pour calculer la dose déposée et ajuster facultativement le traitement.

20. Méthode selon la revendication 19, qui comprend en outre après chaque impulsion de radiation, après peu d'impulsions de radiation, ou après la session de traitement entière, les images de région cibles sont analysées et les informations sur la position, et finalement, la forme de la région cible est utilisée, en association avec les données quant aux impulsions de radiation, pour calculer la dose déposée dans la région cible et dans le mouchoir en papier sain et améliorer le plan de traitement.




FIG. 1




FIG. 2






FIG. 3




FIG. 4





FIG. 5

**FIG. 6**




FIG. 7